



CLEAN AIR PACKAGE(CAP)

Conflo Oil-Injected Desiccant Dryer



General Information	800-1000Cfm CAP	1000-1600Cfm CAP
Dimensions LxWxH (mm)	2000 x 1900 x 2400	2000 x 1900 x 2400
Mass (kg)	2200	3500
Min Air Inlet Pressure	4 Bar	4 Bar
Max Air Inlet Pressure	10 Bar	10 Bar
Pressure Dewpoint	-40°C	-40°C
Used with	800cfm to 1000 cfm Compressor	1000cfm to 1600 cfm Compressor
Inlet Supply (5 meter)	2 " Layflat Hose with 50mm 2" Hosetail Fitting	2 " Layflat Hose with 50mm 2" Hosetail Fitting
Discharge Supply (15 meter)	2 " Layflat Hose with 50mm 2" Hosetail Fitting	2 " Layflat Hose with 50mm 2" Hosetail Fitting
Other features		
Not Stackable	Compact in Size	Forklift Slots
Unit Fitted with inverter 24V to 220V	Heavy Duty Design Manufactured for Site Conditions	High-Quality Dry Air
Integrated DD and PD Filters remove Water, Oil and Particles	Integrated WSD Water Separator	Integrated Aftercooler
Easy Access to Service Points	SANS Government Approved Safety Relieve Valve and Vessel Certificate	

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-17