



OIL SEPERATORS

Large and Small Oil Seperators



General Information		SOS	LOS
Dimensions LxWxH (mm)		580 x 440 x 800	580 x 440 x 800
Mass (kg)		40	60
Used With		D190—D400cfm	D620 –D1200
Maximum Flow (Cfm)		464	1378
Maximum Flow (L/s)		219	650
Max Working Pressure Bar(G)		16	16
Max Working Pressure (Psi)		232	232
Test Pressure Bar(G)		26	26
Maximum Air Temperature (Celcius)		70	70
Discharge Outlet		1 x 50mm Evertite 2" Male Spud with Gasket 2 x 3/4" Chicago Claw Couplings with Gaskets	1 x 50mm Evertite 2" Male Spud with Gasket
Inlet		1 x 50mm Evertite 2" Male Spud with Gasket 2 x 3/4" Chicago Claw Couplings with Gaskets	1 x 50mm Evertite 2" Male Spud with Gasket

Other features

Lifting Eye SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group

Company Reg. No. 2017/250308/07

P.O. Box 13921

Witfield 1467

Atlas Copco House,

Innes Road, Jet Park

Tel: +27 (0) 345 0700

Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-18