



PNS1250

Portable Diesel Oil-Free Screw Compressor: OFH1250



General Information	PNS1250
---------------------	---------

Dimensions LxWxH (mm)	5240 x 2210 x 2350
Mass (Wet - Ready to operate) (kg)	8641
Fuel Tank Capacity (l)	900
Discharge Outlet	80mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	76

Engine	Cummins QSX15	CAT C18
--------	---------------	---------

Power (kW)	395	429
Fuel Consumption (100% load) (l/h)	84	95

Performance	Capacity (Free Air Delivery)		
Working Pressure	cfm	m ³ /min	l/s

Pressure between 6 and 20,4 bar(g)	1250	35	575
Pressure between 20,5 and 24 bar(g)	1200	33	566

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Spillage Free Frame
Hot Air Outlet	Fork Lift Slots & Lifting Eye	Integrated Aftercooler + Water Separator
Spark Arrestor + Inlet Shutdown Valve (Amot)	Ansul Automated Fire Suppression System	Strobe light Indicating Unit is operational
Class Zero Certified (Oil-Free Acc to ISI8573-1)	SANS Government Approved Safety Relieve Valve and Vessel Certificate	Satellite Monitoring System

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com