



ZT132

Electric Driven Oil-Free Screw Compressor: ZT132



General Information ZT132

Dimensions LxWxH (mm)	3400 x 1650 x 2150
Mass (Wet - Ready to operate) (kg)	3850
Discharge Outlet	80mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	79

Engine WEG 400/4355M/L

Main Electric Motor Power (kW)	132
Voltage (V)	400
Frequency (Hz)	50
Start Up Amps (A)	723 A
Full Load Running Amps @ 7-10 bar (A)	241 A
Supply Circuit Breaker (A)	350 A
Electric Supply Cabling	70mm

Performance Capacity (Free Air Delivery)

Working Pressure	cfm	m ³ /min	l/s
Pressure up to 7,5 bar(g)	758	21,5	358

Other features

Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots
Robust & Silent	Water Separator	Elektronikon Touch Display
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com