



XAHS186

Atlas Copco Portable Oil-Injected Screw Compressor: H4012



General Information

Dimensions LxWxH (mm)	4356 x 1716 x 1661
Mass (Wet - Ready to operate) (kg)	1883
Fuel Tank Capacity (l)	180
Discharge Outlet	1 x 50mm Evertite 2" Male Spud with Gasket 3 x 3/4" Chicago Claw Couplings with Gaskets
Sound Pressure Level (7m) dB (A)	73

Engine

Deutz TCD2013 L04

Power (kW)	104
Fuel Consumption (100% load) (l/h)	21

Performance

With and Without Aftercooler

	Working Pressure		Free Air Delivery	
	Bar	Cfm	M ³ /Min	L/s
With After Cooler	12	371	10,5	175
Without After Cooler	12	380	10,7	179

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe Light (Indicating Unit is operational)
Road Worthy with LED Taillights	4-Pole Battery Isolator Switch	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com