



XAMS527

Atlas Copco Portable Oil-Injected Screw Compressor: D1000



General Information

Dimensions LxWxH (mm)	4900 x 2140 x 2480
Mass (Wet - Ready to operate) (kg)	6800
Fuel Tank Capacity (l)	820
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	72

Engine

CATC09

Power (kW)	224
Fuel Consumption (100% load) (l/h)	52

Performance

With and Without Aftercooler

Free Air Delivery

	Bar	Cfm	M ³ /Min	L/s
With After Cooler	8,6	1001	28,3	471
Without After Cooler	8,6	1102	31,2	520

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Forklift slots & Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe Light (Indicating Unit is operational)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com