

XAS137



Atlas Copco Portable Oil-Injected Screw Compressor: D260



General Information

Dimensions LxWxH (mm)	3761 x 1677 x 1479
Mass (Wet - Ready to operate) (kg)	1450
Fuel Tank Capacity (l)	130
Discharge Outlet	3 x 3/4 " Chicago Claw Coupling with Gaskets
Sound Pressure Level (7m) dB (A)	71

Engine

Deutz BF4M2011

Kubota V3800-T

Power (kW)	58	71
Fuel Consumption (100% load) (l/h)	14,1	14,4

Performance

With and Without Aftercooler

	Max Working Pressure		Free Air Delivery	
	Bar	Cfm	M ³ /Min	L/s
With Aftercooler	7	254	7,1	119,8
Without Aftercooler	7	265	7,5	125

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe Light (Indicating Unit is operational)
Road Worthy with LED Taillights	4-Pole Battery Isolator Switch	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-18