



# XATS1200

## Atlas Copco Portable Oil-Injected Screw Compressor: D1200



### General Information

Dimensions LxWxH (mm)	4252 x 2100 x 2500
Mass (Wet - Ready to operate) (kg)	4583
Fuel Tank Capacity (l)	420
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket x 2
Sound Pressure Level (7m) dB (A)	72

### Engine

Cummins DCEC DSL8.9-C360-30

Power (kW)	264
Fuel Consumption (100% load) (l/h)	48,6

### Performance

#### With and Without Aftercooler

	Pressure		Free Air Delivery	
	Bar	Cfm	M <sup>3</sup> /Min	L/s
<b>With After Cooler</b>	5-10,3	1102-1225	34,6-31,5	578-520

### Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator	Spark Arrestor + Inlet Shutdown Valve (Amot)	Strobe Light (Indicating Unit is operational)
Trailer Mounted for Ease of Movement on Site	4-Pole Battery Isolator Switch	SANS Government Approved Safety Relieve Valve and Vessel Certificate

### Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com