



XATS377

Atlas Copco Portable Oil-Injected Screw Compressor: D770



General Information

Dimensions LxWxH (mm)	5074 x 1988 x 2094
Mass (Wet - Ready to operate) (kg)	3450
Fuel Tank Capacity (l)	375
Discharge Outlet	1 x 50mm Evertite 2" Male Spud with Gasket 2 x 3/4 " Chicago Claw Coupling with Gaskets
Sound Pressure Level (7m) dB (A)	72

Engine

CAT C7

Power (kW)	186
Fuel Consumption (100% load) (l/h)	41

Performance

With and Without Aftercooler

	Pressure		Free Air Delivery	
	Bar	Cfm	M ³ /Min	L/s
With After Cooler	10,3	760	21,5	358
Without After Cooler	10,3	785	22,1	368

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe Light (Indicating Unit is operational)
Trailer Mounted for Ease of Movement on Site	4-Pole Battery Isolator Switch	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com