



XATS800

Atlas Copco Portable Oil-Injected Screw Compressor: D800



General Information

Dimensions LxWxH (mm)	4893 X 2010 X2313
Mass (Wet - Ready to operate) (kg)	2800
Fuel Tank Capacity (l)	320
Discharge Outlet	1 x 50mm Evertite 2" Male Spud with Gasket 2 x 3/4 " Chicago Claw Coupling with Gaskets
Sound Pressure Level (7m) dB (A)	72

Engine

Cummins QSB6.7-C260

Power (kW)	194
Fuel Consumption (100% load) (l/h)	45,6

Performance

With and Without Aftercooler

	Pressure		Free Air Delivery	
	Bar	Cfm	M ³ /Min	L/s
With After Cooler	10,3	788	22	372

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator	Spark Arrestor + Inlet Shutdown Valve (Amot)	Strobe Light (Indicating Unit is operational)
Trailer Mounted for Ease of Movement on Site	4-Pole Battery Isolator Switch	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com