



GA110, GA110FF & GA110 VSD FF

Electric Driven Oil-Injected Screw Compressor: Various GA110 Models



General Information	GA110	GA110FF	GA110 VSD FF
Dimensions LxWxH (mm)	2800 x 2000 x 2000	3700 x 2000 x 2000	3700 x 2000 x 2000
Mass (Wet - Ready to operate) (kg)	3100	3500	4015
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket	50mm Evertite 2" Male Spud with Gasket	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	74	74	78
Engine	GA110	GA110FF	GA110 VSD FF
Main Electric Motor Power (kW)	110	110	110
Voltage (V)	400V	400V	400V
Frequency (Hz)	50	50	50
Start Up Amps (A)	440A	440 A	440 A
Full Load Running Amps @ 7-10 bar (A)	220 A	220 A	220 A
Supply Circuit Breaker (A)	300 A	300 A	300 A
Electric Supply Cabling	95mm	95mm	95mm

Performance	Capacity (Free Air Delivery)		
Working Pressure	cfm	m ³ /min	l/s
Pressure up to 7,5 bar(g)	771	21,8	364

Other features		
Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots
Robust & Silent	Water Separator	Elektronikon Touch Display
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-18