



GA200 & GA200FF

Electric Driven Oil-Injected Screw Compressor: GA200 & GA200FF



General Information	GA200	GA200FF
---------------------	-------	---------

Dimensions LxWxH (mm)	3400 x 2000 x 2300	4300 x 2000 x 2300
Mass (Wet - Ready to operate) (kg)	4927	5384
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	78	78

Engine	GA200	GA200FF
--------	-------	---------

Main Electric Motor Power (kW)	200	200
Voltage (V)	400V	400V
Frequency (Hz)	50	50
Start Up Amps (A)	800A	800 A
Full Load Running Amps @ 7-10 bar (A)	400 A	400 A
Supply Circuit Breaker (A)	500 A	500 A
Electric Supply Cabling	120mm	120mm

Performance	Capacity (Free Air Delivery)		
Working Pressure	cfm	m ³ /min	l/s

Pressure up to 7,5 bar(g)	1428	40,43	673,6
---------------------------	------	-------	-------

Other features		
----------------	--	--

Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots
Robust & Silent	Water Separator	Elektronikon Touch Display
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com