



GA250 400V & 525V

Electric Driven Oil-Injected Screw Compressor: GA250 400V & 525V



General Information	GA250 400V	GA250 525V
---------------------	------------	------------

Dimensions LxWxH (mm)	3386 x 2120 x 2400	3386 x 2120 x 2400
Mass (Wet - Ready to operate) (kg)	5017	5017
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	75	78

Engine	GA250 400V	GA250 525V
--------	------------	------------

Main Electric Motor Power (kW)	250	250
Voltage (V)	400V	525V
Frequency (Hz)	50	50
Start Up Amps (A)	1200A	1100 A
Full Load Running Amps @ 7-10 bar (A)	440 A	380 A
Supply Circuit Breaker (A)	500 A	500 A
Electric Supply Cabling	2 x 120mm	1 x 120mm

Performance	Capacity (Free Air Delivery)		
Working Pressure	cfm	m ³ /min	l/s

Pressure up to 7,5 bar(g)	1548	43,83	730,1
---------------------------	------	-------	-------

Other features		
----------------	--	--

Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots
Robust & Silent	Water Separator	Elektronikon Touch Display
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-18