



GA37, GA37FF & GA37 VSD FF

Electric Driven Oil-Injected Screw Compressor: Various GA37 Models



General Information	GA37	GA37FF	GA37 VSD FF
---------------------	------	--------	-------------

Dimensions LxWxH (mm)	1395 x 865 1625	1395 x 865 x 1625	1395 x 865 x 1625
Mass (Wet - Ready to operate) (kg)	787	1120	1120
Discharge Outlet	3/4 " Chicago Claw Coupling with Gaskets	3/4 " Chicago Claw Coupling with Gaskets	3/4 " Chicago Claw Coupling with Gaskets
Sound Pressure Level (7m) dB (A)	69	65	65

Engine	GA37	GA37FF	GA37 VSD FF
--------	------	--------	-------------

Main Electric Motor Power (kW)	37	37	37
Voltage (V)	400V	400V	400V
Frequency (Hz)	50	50	50
Start Up Amps (A)	180 A	180 A	180 A
Full Load Running Amps @ 7-10 bar (A)	75 A	75 A	75 A
Supply Circuit Breaker (A)	125 A	125 A	125 A
Electric Supply Cabling	35mm	35mm	35mm

Performance	Capacity (Free Air Delivery)		
-------------	------------------------------	--	--

Working Pressure	cfm	m ³ /min	l/s
Pressure up to 7,5 bar(g)	250	7,1	117

Other features		
----------------	--	--

Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots
Robust & Silent	Water Separator	Elektronikon Touch Display
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-18