



GR200FF

Electric Driven Oil-Injected Screw Compressor: GR200FF



General Information GR200FF

Dimensions LxWxH (mm)	2779 x 1886 x 2010
Mass (Wet - Ready to operate) (kg)	3877
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	75

Engine GR200FF

Main Electric Motor Power (kW)	200
Voltage (V)	400V
Frequency (Hz)	50
Start Up Amps (A)	800 A
Full Load Running Amps @ 7-10 bar (A)	400 A
Supply Circuit Breaker (A)	500 A
Electric Supply Cabling	120mm

Performance Capacity (Free Air Delivery)

Working Pressure	cfm	m ³ /min	l/s
Pressure up to 20 bar(g)	816	23,1	385

Other features

Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots
Robust & Silent	Water Separator	Elektronikon Touch Display
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com