

XRVS1050

Atlas Copco Portable High Pressure
Oil-Injected Screw Compressor: H952



General Information

Dimensions LxWxH (mm)	4908 x 2140 x 2499
Mass (Wet - Ready to operate) (kg)	5754
Fuel Tank Capacity (l)	796
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	108

Engine

Power (kW)	315
Fuel Consumption (100% load)/ (L/h)	77

Performance

Max Working Pressure			Free Air Delivery	
PSI	Bar	Cfm	M ³ /Min	L/s
365	25	1050	29,7	495

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Forklift Slots & Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe light (Indicating Unit is operational)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame	SANS Government Approved Safety Relieve Valve and Vessel Certificate



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.