

XRVS476

Atlas Copco Portable Oil-Injected
Screw Compressor: H952



General Information

Dimensions LxWxH (mm)	5640 x 2100 x 2460
Mass (Wet - Ready to operate) (kg)	6843
Fuel Tank Capacity (l)	796
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	72

Engine

CAT C13

Power (kW)	317
Fuel Consumption (100% load) (l/h)	63

Performance

With and Without Aftercooler

	Bar	Cfm	Free Air Delivery	
			M ³ /Min	L/s
With After Cooler	25	975	27,6	459
Without After Cooler	25	953	26,9	449

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Forklift Slots & Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe light (Indicating Unit is operational)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame	SANS Government Approved Safety Relieve Valve and Vessel Certificate



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.