

# XRVS487

Atlas Copco Portable Oil-Injected  
Screw Compressor: H952



## General Information

Dimensions LxWxH (mm)	5650 x 2150 x 2500
Mass (Wet - Ready to operate) (kg)	5970
Fuel Tank Capacity (l)	796
Discharge Outlet	50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	76

## Engine

CAT C13

Power (kW)	328
Fuel Consumption (100% load) (l/h)	63

## Performance

With Aftercooler

	Bar	Cfm	M <sup>3</sup> /Min	L/s
Free Air Delivery	25	1051	29,8	496

## Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Forklift Slots & Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe light (Indicating Unit is operational)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame	SANS Government Approved Safety Relieve Valve and Vessel Certificate



AIR



POWER



TEMPERATURE



FLOW

[www.randair.com](http://www.randair.com)

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.  
Please contact your nearest Rental office for detailed application advice.