



Y1260

Atlas Copco Portable Oil-Injected Screw Compressor: H1235



General Information

Dimensions LxWxH (mm)	5000 x 2250 x 2510
Mass (Wet - Ready to operate) (kg)	7150
Fuel Tank Capacity (l)	876
Discharge Outlet	1 x 50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	76

Engine

CAT C18

Power (kW)	478
Fuel Consumption (100% load) (l/h)	48-82

Performance

Variable Pressure

Free Air Delivery

Bar	Psi	Cfm	M ³ /Min	L/s
15	304,5	1431	40,5	648
35	507,6	1126	31,8	580

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe Light (Indicating Unit is operational)
4-Pole Battery Isolator Switch	Sound attenuated muffler inside	SANS Government Approved Safety Relieve Valve and Vessel Certificate

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com