

QAS500

Atlas Copco QAS500 Silenced
Generator: G500



General Information (50Hz | 60Hz)

Rated Frequency	Hz	50 60	Sound Power Level (LwA)	dB (A)	97 100
Rated Voltage	V	400 480	Min/Max Ambient	°C	-25/50
Prime Rated Power	kVA/kW	500/400 587/470	Fuel Consumption @ 75% Load to 100% Load (l/hr)	l/hr	77 to 102.6 89 to 118.6
Rated Current	A	722 706	Fuel Tank Capacity	l	970

Dimensions

Trailer-Mounted			Removed from Trailer		
Size (L x W x H)	mm	6100 x 2450 x 2800	Size (L x W x H)	mm	4800 x 1550 x 2290
Mass - Dry	kg	6694	Mass - Dry	kg	5594
Mass - Wet	kg	7526	Mass - Wet	kg	6426

Optional Accessories

Cables – 20m (Recommended 2 x 50mm 5 Core)	Transformers
Distribution Boards	External Fuel Tanks

Other Features

9 Kg Fire Extinguisher	Automatic Mains Failure (AMF) (Only for certain models)
Buzz Bar	Strobe Light (Indicating units is operational)
External Fuel Tank Connection (Only for certain models)	Emergency Stop Switch
Paralleling with Compatible Generators	Remote and Auto Start (Only for certain models)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame
4-Pole Battery Isolator Switch	



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.

QAS325

Atlas Copco QAS305/325 Silenced
Generator: G300



General Information (50Hz | 60Hz)

Rated Frequency	Hz	50 60	Sound Power Level (LwA)	dB (A)	97 99
Rated Voltage	V	400 480	Min/Max Ambient	°C	-25/50
Prime Rated Power	kVA/kW	325/260 345/276	Fuel Consumption @ 75% Load to 100% Load (l/hr)	l/hr	51 to 68 53.3 to 71
Rated Current	A	469 415	Fuel Tank Capacity	l	640

Dimensions

Trailer-Mounted			Removed from Trailer		
Size (L x W x H)	mm	4400 x 2450 x 24500	Size (L x W x H)	mm	4020 x 1390 x 2020
Mass - Dry	kg	5135	Mass - Dry	kg	4185
Mass - Wet	kg	5685	Mass - Wet	kg	4735

Optional Accessories

Cables – 20m (Recommended 1 x Set of 185mm 4 Core + 1 x 95mm Earth)	Transformers
Distribution Boards	External Fuel Tanks

Other Features

9 Kg Fire Extinguisher	Automatic Mains Failure (AMF) (Only for certain models)
Buzz Bar	Strobe Light (Indicating units is operational)
External Fuel Tank Connection (Only for certain models)	Emergency Stop Switch
Paralleling with Compatible Generators	Remote and Auto Start (Only for certain models)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame
4-Pole Battery Isolator Switch	Distribution Board on Trailer or Separate



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.

QAS200

Atlas Copco QAS200 Silenced
Generator: G200



General Information (50Hz | 60Hz)

Rated Frequency	Hz	50 60	Sound Power Level (LwA)	dB (A)	97 99
Rated Voltage	V	400 480	Min/Max Ambient	°C	-25/50
Prime Rated Power	kVA/kW	200/160 225/180	Fuel Consumption @ 75% Load to 100% Load (l/hr)	l/hr	23 to 30.6 29.3 to 39
Rated Current	A	288 270	Fuel Tank Capacity	l	360

Dimensions

Trailer-Mounted			Removed from Trailer		
Size (L x W x H)	mm	4900 x 2000 x 2800	Size (L x W x H)	mm	3770 x 1200 x 1880
Mass - Dry	kg	3689	Mass - Dry	kg	2889
Mass - Wet	kg	4092	Mass - Wet	kg	3292

Optional Accessories

Cables – 20m (Recommended 2 x 50mm 5 Core)	Transformers
Distribution Boards	External Fuel Tanks

Other Features

9 Kg Fire Extinguisher	Automatic Mains Failure (AMF) (Only for certain models)
Buzz Bar	Strobe Light (Indicating units is operational)
External Fuel Tank Connection (Only for certain models)	Emergency Stop Switch
Paralleling with Compatible Generators	Remote and Auto Start (Only for certain models)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame
4-Pole Battery Isolator Switch	Super Silent (65 dB (A))



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.

QAS150

Atlas Copco QAS150 Silenced
Generator: G150



General Information (50Hz | 60Hz)

Rated Frequency	Hz	50 60	Sound Power Level (LwA)	dB (A)	96 99
Rated Voltage	V	400 480	Min/Max Ambient	°C	-25/50
Prime Rated Power	kVA/kW	150/120 171/137	Fuel Consumption @ 75% Load to 100% Load (l/hr)	l/hr	23 to 30.6 29.3 to 39
Rated Current	A	216 206	Fuel Tank Capacity	l	360

Dimensions

Trailer-Mounted			Removed from Trailer		
Size (L x W x H)	mm	4900 x 2000 x 2300	Size (L x W x H)	mm	3380 x 1180 x 1700
Mass - Dry	kg	3100	Mass - Dry	kg	2300
Mass - Wet	kg	3410	Mass - Wet	kg	2610

Optional Accessories

Cables – 20m (Recommended 2 x 50mm 5 Core)	Transformers
Distribution Boards	External Fuel Tanks

Others Features

9 Kg Fire Extinguisher	Automatic Mains Failure (AMF) (Only for certain models)
Buzz Bar	Strobe Light (Indicating units is operational)
External Fuel Tank Connection (Only for certain models)	Emergency Stop Switch
Paralleling with Compatible Generators	Remote and Auto Start (Only for certain models)
Trailer Mounted for Ease of Movement on Site	Spillage Free Frame
4-Pole Battery Isolator Switch	Distribution Board on Trailer or Separate



www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.