

QLB6

Atlas Copco QLB6 Silenced Lighting Tower: QLB6



General Information			
Dimensions LxWxH (mm) (Trailer Mounted)		3400 x 1800 x 2900	
Mass (Wet - Ready to operate) (kg) (Trailer Mounted)		1600	
Fuel Tank Capacity (I)		140	
Fuel Consumption at 75% Load (I/hr) to 100% Load (I/hr)		0,5	
Frequency (Hz)		50	
Prime Rated Power (Kva/KW)		2,7	
Voltage (V)		230	
Luminosity		5,4Lm/m2 (0.5Fc @ 7 Acres)	
Sound Power Level LWA dB (A)		88	
Min/Max Ambient ('C)		-18/50	
Engine		Hatz	
Power (kW)		3,5	
Other features			
9 Kg Fire Extinguisher	4-Pole Battery Isolator Switch		Trailer Mounted and Easy to Move
Road Worthy with LED Lights	Compact, Robust and Versatile		Unit to Mine Specifications
360 Degrees Rotation of Mast	Smartmast Automated Mast		LED 4 X 350W
Remote Start via Photocell or Weekly Timer	Twin Strobe Light (Indicating Unit is Operational)		Spillage Free Frame for Fluid Containment
Rand Air South Africa (Pty) Ltd			
Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com