

## **QAC1450**

## Atlas Copco QAC1450 Silenced Generator: Twinpower



General Information		50Hz		60Hz	
Dimensions LxWxH (mm)		6060 x 2500 x 2600		6060 x 2500 x 2600	
Mass (Wet - Ready to operate) (kg)		16 500		16 500	
Fuel Tank Capacity (I)		1640		1640	
Fuel Consumption at 75% Load (I/hr) to 100% Load (I/hr)		211 to 275		217 to 288	
Frequency (Hz)		50		60	
Prime Rated Power (Kva/KW)		1447 / 1158		1447 / 1158	
Voltage (V)		400		480	
Nominal Current (A)		2089		1741	
Sound Power Level LWA dB (A)		72		73	
Min/Max Ambient ('C)		-18/50		-18/50	
Additional Accessories					
Cables (Recommended <b>6</b> sets of 185mm 4 core + 1 x 95mm Earth Cable)	Distribut	ion Boards	Transformers	External Fu	el Tanks
Other features					
9 Kg Fire Extinguisher	4-Pole Battery Isolator Switch		E	Emergency Stop Switch	
Buzz Bar	Automatic Mains Failure (AMF) (Certain Fleet Models only)			Remote and Auto Start (Certain Fleet Models only)	
External Fuel Tank Connection (Certain Flee Models only)	Strobe Light (Indicating units is operational)		ational) S	Spillage Free Frame	
Parallelling with Compatible Generators	Specialized Eye Lifting Hooks				
Rand Air South Africa (Pty) Ltd					
Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,		Tel: +27 (0) 345 0700	
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park		Info@randair.com	