

QAS250



Atlas Copco QAS250 Silenced Generator: G250



General Information	50Hz	60Hz
Dimensions LxWxH (mm) (Trailer Mounted)	5170 x 2000 x 2700	5170 x 2000 x 2700
Mass (Wet - Ready to operate) (kg) (Trailer Mounted)	3820	3820
Dimensions LxWxH (mm) (Removed from Trailer)	3770 x 1200 x 1870	3770 x 1200 x 1870
Mass (Wet - Ready to operate) (kg) (Removed from Trailer)	3283	3283
Fuel Tank Capacity (l)	496	496
Fuel Consumption at 75% Load (l/hr) to 100% Load (l/hr)	38,6 to 51,4	42 to 56
Frequency (Hz)	50	60
Prime Rated Power (Kva/KW)	250 / 200	255 / 204
Voltage (V)	400	480
Nominal Current (A)	360	360
Sound Power Level LWA dB (A)	70	70
Min/Max Ambient (°C)	-18/50	-18/50

Additional Accessories

Cables (Recommended 1 x Set of 185mm 4 Core + 1 x 95mm Earth)	Distribution Boards	Transformers	External Fuel Tanks
--	---------------------	--------------	---------------------

Other features

9 Kg Fire Extinguisher	4-Pole Battery Isolator Switch	Emergency Stop Switch
Buzz Bar	Automatic Mains Failure (AMF) (Certain Fleet Models only)	Remote and Auto Start (Certain Fleet Models only)
External Fuel Tank Connection (Certain Fleet Models only)	Strobe Light (Indicating units is operational)	Spillage Free Frame
Trailer Mounted for Ease of Movement on Site	Paralleling with Compatible Generators	

Rand Air South Africa (Pty) Ltd

Part of the Atlas Copco Group	P.O. Box 13921	Atlas Copco House,	Tel: +27 (0) 345 0700
Company Reg. No. 2017/250308/07	Witfield 1467	Innes Road, Jet Park	Info@randair.com

For Information Only. Subject to change without notice. Information is for guidance only contact your nearest rental office for application advice .

2021-11-18