



QAS80

Atlas Copco QAS80 Silenced Generator: G080



| General Information | 50Hz | 60Hz |
|--|--------------------|--------------------|
| Dimensions LxWxH (mm) (Trailer Mounted) | 5000 x 1630 x2100 | 5000 x 1630 x2100 |
| Mass (Wet - Ready to operate) (kg) (Trailer Mounted) | 2250 | 2250 |
| Dimensions LxWxH (mm) (Removed from Trailer) | 2850 x 1100 x 1635 | 2850 x 1100 x 1635 |
| Mass (Wet - Ready to operate) (kg) (Removed from Trailer) | 1994 | 1994 |
| Fuel Tank Capacity (l) | 230 | 230 |
| Fuel Consumption at 75% Load (l/hr) to 100% Load (l/hr) | 14,9 to 19,8 | 19 to 23,8 |
| Frequency (Hz) | 50 | 60 |
| Prime Rated Power (Kva/KW) | 80 / 64 | 93/74,4 |
| Voltage (V) | 400 | 480 |
| Nominal Current (A) | 115,5 | 111,9 |
| Sound Power Level LWA dB (A) | 67 | 67 |
| Min/Max Ambient (°C) | -18/50 | -18/50 |

Additional Accessories

| | | |
|--------------------------------------|---------------------|--------------|
| Cables (Recommended 1 x 50mm 5 Core) | Distribution Boards | Transformers |
|--------------------------------------|---------------------|--------------|

Other features

| | | |
|---|---|---|
| 9 Kg Fire Extinguisher | 4-Pole Battery Isolator Switch | Emergency Stop Switch |
| Buzz Bar | Automatic Mains Failure (AMF) (Certain Fleet Models only) | Remote and Auto Start (Certain Fleet Models only) |
| External Fuel Tank Connection (Certain Fleet Models only) | Strobe Light (Indicating units is operational) | Spillage Free Frame |
| Trailer Mounted for Ease of Movement on Site | Road-Worthy with LED Tail Lights | |

Rand Air South Africa (Pty) Ltd

| | | | |
|---------------------------------|----------------|----------------------|-----------------------|
| Part of the Atlas Copco Group | P.O. Box 13921 | Atlas Copco House, | Tel: +27 (0) 345 0700 |
| Company Reg. No. 2017/250308/07 | Witfield 1467 | Innes Road, Jet Park | Info@randair.com |