

XAS137

Atlas Copco Portable Oil-Injected
Screw Compressor: D260



General Information

Dimensions LxWxH (mm)	3761 x 1677 x 1479
Mass (Wet - Ready to operate) (kg)	1450
Fuel Tank Capacity (l)	130
Discharge Outlet	3 x 3/4 " Chicago Claw Coupling with Gaskets
Sound Pressure Level (7m) dB (A)	71

Engine

Deutz BF4M2011

Kubota V3800-T

Power (kW)	58	71
Fuel Consumption (100% load) (l/h)	14,1	14,4

Performance

With and Without Aftercooler

	Max Working Pressure		Free Air Delivery	
	Bar	Cfm	M³/Min	L/s
With Aftercooler	7	254	7,1	119,8
Without Aftercooler	7	265	7,5	125

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe Light (Indicating Unit is operational)
Road Worthy with LED Taillights	4-Pole Battery Isolator Switch	SANS Government Approved Safety Relieve Valve and Vessel Certificate



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.

XAS186

Atlas Copco Portable Oil-Injected
Screw Compressor: D400



General Information

Dimensions LxWxH (mm)	3941 x 1701 x 1661
Mass (Wet - Ready to operate) (kg)	1825
Fuel Tank Capacity (l)	175
Discharge Outlet	3 x 3/4 " Chicago Claw Coupling with Gaskets & 1 x 50mm Evertite 2" Male Spud with Gaskets
Sound Pressure Level (7m) dB (A)	71

Engine

Deutz BF4M2012C

Power (kW)	88
Fuel Consumption (100% load) (l/h)	18

Performance

With and Without Aftercooler

Max Working Pressure		Free Air Delivery		
Bar	Psi	Cfm	M ³ /Min	L/s
7	102	392	11,1	185

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe Light (Indicating Unit is operational)
Road Worthy with LED Taillights	4-Pole Battery Isolator Switch	SANS Government Approved Safety Relieve Valve and Vessel Certificate



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.

XAHS186

Atlas Copco Portable Oil-Injected
Screw Compressor: H4012



General Information

Dimensions LxWxH (mm)	4356 x 1716 x 1661
Mass (Wet - Ready to operate) (kg)	1883
Fuel Tank Capacity (l)	180
Discharge Outlet	1 x 50mm Evertite 2" Male Spud with Gasket
Sound Pressure Level (7m) dB (A)	73

Engine

Deutz TCD2013 L04

Power (kW)	104
Fuel Consumption (100% load) (l/h)	21

Performance

With and Without Aftercooler

Free Air Delivery

	Bar	Cfm	M ³ /Min	L/s
With After Cooler	12	371	10,5	175
Without After Cooler	12	380	10,7	179

Other features

9 Kg Fire Extinguisher	Emergency Stop Switch	Lifting Eye
Integrated Aftercooler + Water Separator (Certain Fleet Models)	Spark Arrestor + Inlet Shutdown Valve (Amot) (Certain Fleet Models)	Strobe Light (Indicating Unit is operational)
Road Worthy with LED Taillights	4-Pole Battery Isolator Switch	SANS Government Approved Safety Relieve Valve and Vessel Certificate



AIR



POWER



TEMPERATURE



FLOW

www.randair.com

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.
Please contact your nearest Rental office for detailed application advice.