

# XRHS930E

Electric Driven Oil-Injected Screw  
Compressor: XRHS930E



General Information		XRHS930E	
Dimensions LxWxH (mm) Wagon (Tow Raised)		4300 x 2100 x 2700	
Mass (Wet - Ready to operate) (kg)		5615	
Discharge Outlet		50mm Evertite 2" Male Spud with Gasket	
Sound Pressure Level (7m) dB (A)		80	
Engine		XRHS930E	
Main Electric Motor Power (kW)		230	
Voltage (V)		400V	
Frequency (Hz)		50	
Start Up Amps (A)		1250 A	
Full Load Running Amps @ 7-20 bar (A)		440 A	
Supply Circuit Breaker (A)		650 A	
Electric Supply Cabling		2 x 120mm	
Performance		Capacity (Free Air Delivery)	
Working Pressure	cfm	m <sup>3</sup> /min	l/s
Pressure up to 20 bar(g)	937	26.7	442
Other features			
Emergency Stop Switch	Reliable Motor & Drive Train	Fork Lift Slots	
Robust & Silent	Water Separator	Elektronikon Touch Display	
Fitted with Phase Protection Relay	Integrated Aftercooler (Certain Fleet Models only)	SANS Government Approved Safety Relieve Valve and Vessel Certificate	



AIR



POWER



TEMPERATURE



FLOW

[www.randair.com](http://www.randair.com)

Rand-Air South Africa (Pty) Ltd.

Subject to change without prior notice. Information is for guidance only.  
Please contact your nearest Rental office for detailed application advice.